

Use: hot and cold sanitary water circuits, pressurizing systems, heating systems and refrigeration circuits

Features

- Multipurpose expansion tank for hot and cold sanitary water circuits, pressurizing systems, heating systems and refrigeration circuits
- Ideal solution to optimize spaces in HVACR systems
- Interchangeable membrane realized in accordance with DIN 4807
- 100% made in Italy
- Produced according to the standards established by PED 2014/68/UE and EN 13831 regulations
- Homologations: WRAS, ACS
- High level of customization
- Epoxy powder exterior painting to guarantee a high level of protection against oxidation and a fine aesthetic final quality
- Accurate and extensive first-rate quality controls during all manufacturing process phases



Code	Model	Capacity	Diameter	Height	Water entry connection	Membrane	Standard pre-loading pressure	Maximum working pressure	Working temperature	External finishing colour
		Liters	Ø mm	H mm	G			Bar	°C	
45005	STYLE 0,5	0,5	80	198	M 1/2" Gas	Rubber	3,5	16,0	-10 + 100	Grey
4501	STYLE 1	1	80	270	M 1/2" Gas	Rubber	3,5	16,0	-10 + 100	Grey
4502	STYLE 2	2	80	440	M 1/2" Gas	Rubber	3,5	16,0	-10 + 100	Grey
450201	STYLE 2 d.90	2	90	335	M 1/2" Gas	Rubber	3,5	16,0	-10 + 100	Grey

4503	STYLE 3	3	90	560	M 1/2" Gas	Rubber	3,5	16,0	-10 + 100	Grey
4503120	STYLE 3 d.120	3	120	300	M 1/2" Gas	Rubber	3,5	16,0	-10 + 100	Grey
4504	STYLE 4	4	90	655	M 1/2" Gas	Rubber	3,5	10,0	-10 + 100	Grey
4504120	STYLE 4 d.120	4	120	400	M 1/2" Gas	Rubber	3,5	10,0	-10 + 100	Grey
4505	STYLE 5 d.120	5	120	510	M 1/2" Gas	Rubber	3,5	10,0	-10 + 100	Grey
4506	STYLE CE 6	6	120	600	M 1/2" Gas	Rubber	3,5	10,0	-10 + 100	Grey
4508120	STYLE CE 8 d.120	8	120	760	M 1/2" Gas	Rubber	3,5	10,0	-10 + 100	Grey
4508	STYLE CE 8	8	160	515	M 1/2" Gas	Rubber	3,5	10,0	-10 + 100	Grey
4512	STYLE CE 12	12	160	650	M 3/4" Gas	Rubber	3,5	10,0	-10 + 100	Grey
4515	STYLE CE 15	15	160	750	M 3/4" Gas	Rubber	3,5	10,0	-10 + 100	Grey
4518	STYLE CE 18	18	220	570	M 3/4" Gas	Rubber	3,5	10,0	-10 + 100	Grey