


Identification Codes



Tank



Model	Max. Pressure (bar)	Nominal Capacity (L)	Actual Capacity (L)	Membrane	Max. Temp	Connection
24ST	8	24	20	EPDM	99°C	G1"
24STT	8	24	24	EPDM	99°C	G1"

The service life of the membrane is 50,000 cycles.

Model	Max. Pressure (bar)	Nominal Capacity (L)	Actual Capacity (L)	Membrane	Max. Temp	Connection
2VT	8	2	2	EPDM	99°C	G1/2"
4VT	8	4	4	EPDM	99°C	G1"
8VT	8	8	8	N.R	99°C	G1"
19VT	8	19	18	EPDM	99°C	G1"
24VT	8	24	20	EPDM	99°C	G1"
24VTT	8	24	24	EPDM	99°C	G1"

The service life of the membrane is 50,000 cycles.

Model	Max. Pressure (bar)	Nominal Capacity (L)	Actual Capacity (L)	Membrane	Max. Temp	Connection
19CT	8	19	18	EPDM	99°C	G1"
24CT	8	24	20	EPDM	99°C	G1"
24CTT	8	24	24	EPDM	99°C	G1"
50CT	8	50	36	EPDM	99°C	G1"
50CTT	8	50	50	EPDM	99°C	G1"
60CTT	8	60	60	EPDM	99°C	G1"
100CT	8	100	80	EPDM	99°C	G1"
100CTT	8	100	100	EPDM	99°C	G1"

The service life of the membrane is 50,000 cycles.

Model	Max. Pressure (bar)	Nominal Capacity (L)	Actual Capacity (L)	Membrane	Max. Temp	Connection
50FT	8	50	36	EPDM	99°C	G1"
50FTT	8	50	50	EPDM	99°C	G1"
60FTT	8	60	60	EPDM	99°C	G1"
100FT	8	100	80	EPDM	99°C	G1"
100FTT	8	100	100	EPDM	99°C	G1"

The service life of the membrane is 50,000 cycles.

3-Way/5-Way



5TA 5TB 3TA

Model	Connection	Length
3TA	G1"	70, 80, 90
5TA	G1"	70, 80, 90
5TB	G1"	70, 80, 90

Foot Valve



FVA

Model	Connection
FVA1	1"
FVA1.25	1 1/4"
FVA1.5	1 1/2"
FVA2	2"
FVA3	3"

- Stainless steel mesh
- Can be used as a check valve

Flexible Hose



	FH12.8-01 (L=128mm)	FH44-03 (L=440mm)
Inlet	G7/8"	G1"
Outlet	G3/8"	G1"
Material	Stainless steel wire	Stainless steel wire
	Fluid temperature up to 35°C; Maximum ambient temperature 40°C.	

Filter



	WF-01A	WF-02A
	1" x 1"	1" x 1"
	1L	2L
	5bar	5bar
	Fluid temperature up to 35°C; Maximum ambient temperature 40°C.	